


## **NEO-1 Wireless Temperature and Humidity Sensor**

NEO-1 is a sensor and a data logger that can wirelessly monitor temperature, humidity, VPD, Heat Index, Dew Points for up to 3+ years on battery power and send security alerts to your smartphone and the iMatrix Cloud.



This BLE sensor boasts high precision sensors with an accuracy of  $\pm 0.3^{\circ}$ C for temperature and  $\pm 3\%$  for humidity, ensuring reliable data. It is capable of storing over 100K data points, equivalent to one month of sensor data at 1-minute intervals. Users can customize time intervals, set real-time alerts, review historical data, and generate compliance reports.

The iMatrix NEO-1 temperature and humidity sensor delivers accurate, comprehensive logs sent directly to your smartphone or accessible via the iMatrix Cloud. This sensor offers an exceptional solution for monitoring climate-sensitive environments.

With its compact size  $(2.78 \times 1.5 \times 0.7 \text{ in} / 70.6 \times 38 \times 17.8 \text{ mm})$ , lightweight design (1.34 oz / 38 grams), and IP66 waterproof rating, it is perfect for monitoring cold chain shipments, refrigeration systems, greenhouses, RVs, wine cellars, cigars, musical instruments, and pharmaceuticals.

## **Key Features**

- Get 24 hours a day monitoring with real-time alerts, logs, and reports
- Connect to iMatrix Cloud for World Wide Access
- Manage multiple sensors in multiple locations
- Set and receive alerts directly to smartphone or optionally use the Wi-Fi Micro Gateway (sold separately)
- Organize thousands of sensors with multiple groups & locations
- Upload sensor data to the iMatrix Cloud automatically in real-time with iMatrix SensorMonitor Smartphone App
- Setup sensors in one step scan QR code with App and you're monitoring



## Overview

- Temperature -40°F to 158°F (-40°C to 70°C) (+/- 0.3°C)
- Humidity 0% to 100% (+/- 3%)
- Bluetooth (BLE) 5.2
- Range 100 meters / 330 feet
- Stores 100,000+ data points
- Dimensions 2.78 x 1.5 x 0.7 in (70.6 x 38 x 17.8 mm)
- Weight 1.34 oz (38 grams)
- IP66 waterproof rating
- Battery life up to 3 years
- Powered by 2 Lithium AAA batteries (1100 mAh)
- FCC,CE,QDID/EPL











Get NEO-1 at:

https://imatrixsys.com/neo-1/

Ordering part number: NEO-1

